


Technical Data

Model			
	PV0191-1P-A PV0191-1P		HDKDC1P32AL
Rated Voltage	1000VDC		1500VDC
Rated Current	32A		50A
Size of Fuse Link	10x38mm		14x85mm
Class of Operation	gPV		gPV
Mechanical Life	500		500
Product Width	18mm		22mm
Tightening Torque	2.5Nm 14In-lbs		2.5Nm 14In-lbs
Terminal size for Cable	6mm² 8-18AWG		10mm² 6-18AWG
Ambient temperature (with daily average≤35°C)	-5°C~+40°C		
Storage Temperature	-25°C~+70°C		
Standard:	IEC60269-6		
Mounting	On DIN rail EN60715(35mm) by means of fast clip device		

Reference No.	DC Voltage Grade	Size of Fuse Link	Current Rating for Fuse Link
PV0191-1P-A	1000VDC	10x38mm	1,2,3,4,5,6,8,10,12,15,16,20,25,30,32A
PV0191-1P	1000VDC	10x38mm	1,2,3,4,5,6,8,10,12,15,16,20,25,30,32A
HDKDC1P32AL	1500VDC	14x85mm	8,10,12,15,16,20,25,30,32,35,40,45,50A

Overall and Installation Dimension(mm)

PV0191-1P-A



PV0191-1P

