

ATTESTATION OF CONFORMITY

Issued to: DAH New Energy Technology Co., Ltd.
4th Floor, Office Building, 1 yao yuan Road, Luyang Industrial Park, Luyang District,
Hefei City, Anhui Province ,China

For the product: Rechargeable Li-ion Battery

Trade name: 

Type/Model: DHN-HVRES16L-G1, DHN-HVRES16R-G1

Ratings: See model list

Manufactured by: DAH New Energy Technology Co., Ltd.
4th Floor, Office Building, 1 yao yuan Road, Luyang Industrial Park, Luyang District,
Hefei City, Anhui Province ,China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 61000-6-2:2019
EN IEC 61000-6-4:2019

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no. 6250307.50V1.1

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive 2014/30/EU.


The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 19 January 2026

Number: 6250307.01AOCV1.1

DEKRA Testing and Certification (Shanghai) Ltd.


Kreny Lin
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2

DEKRA Testing and Certification (Shanghai) Ltd.
5F #250 Jiangchangsan Road Shibei Hi-Tech Park, 200436 Jing'an District, Shanghai, China
T +86 21 6056 7666 F +86 21 6056 7555 www.dekra-product-safety.com

Annex

Document no. : 6250307.01AOCV1.1

Model list:

Model	DHN-HVRES16L-G1	DHN-HVRES16R-G1
Battery Designation	IFpP73/175/209 [1P16S]M/-20+50/95	
Operating Voltage	40 ~ 58.4 Vdc	
Nominal Voltage	51.2 Vdc	
Rated Capacity	314 Ah	
Rated Energy	16077 Wh	
Charging Temperature Range	0°C ~ 50°C	
Discharging Temperature Range	-20°C ~ 55°C	
Recommended Discharge/Charge Current	157 Adc	

End